


CONTRAK FOLDING VENTED or UNVENTED BIN



CONTRAK FOLDING BIN SPECIFICATIONS

- External dimensions 1162mm x 1162mm x 780mm high
- Internal dimensions 1090mm x 1080mm x 635mm high
- Bin tare weight 49 kg
- Folded height 280mm
- Volume capacity is 750 litre
- Each unit has two drop gates which are 860mm wide and 300mm high
- 2 way forklift access; access height and width 95mm x 862mm
- Stacking recess is 13mm
- Suitable for temperature of -20°C to +40°C
- Friction pads on bearers (5 per side) and pads also on base (3 per side)
- Load carrying capacity 500kg , static = 3,000 kg , dynamic = 1,000 kg
- Racking locator recess is 10mm deep (twice on each side) Total bearer length is 1162mm made up of 2 x 225mm long x 10mm deep racking locator recesses and both are located 158mm from each end
- Four label locators one on each gate; two further label locators on inside of fold down gates for content identification when gate is open
- 3 logo inserts on the front and back of the base gate sides
- Drain holes to be located in the middle of the floor base
- Bin is RFID enabled with tag size of up to 200mm able to be placed inside of the bearer foot.
- Bin can be supplied in vented or unvented form with vents being 10mm wide x 40mm high

Interested and require more information? Please contact your local representative or email us at sales@sbhsolutions.com.au