Supplied by

Phone: (08) 7122 1114 / Email: info@sbhsolutions.com.au













See www.schoellerallibert.com for additional material like Handling Instructions View Video

Accessories





A193690100 - Bayonet Socket CE/CF/ M0/CFlow/BPac





2550801 - MO 1210 Bayonet Plug

2538000 - Optiframe 1200x1000 (set 1LS + 1SS)

Related Products



9347000 - Magnum Optimum 1210 Lid 1200x1000x50



997509D - FLC Dust Cover 1210

Magnum Optimum 1200x1000x975 - 2R 2DD

ltem: 2549461 **∏"**

The Magnum Optimum® 1210 is the strongest FLC on the market. It is suitable for use in a variety of applications in almost any market. Maximized usable volume thanks to its double-wall structure design. With the highest folding ratio on the market, M01210 stacks up to 8 in a standard truck and 10 high in a mega truck. The unique push self-lock doors enable easy loading and unloading. Strap locations and pins in the base angles enable secure loading. Available in a variety of heights, base and sidewall configurations. Accessories such as a lid and unique Optiframe® available. One single Optiframe® increases height and volume to fit dunnage systems when empty or maximize vehicle fill in increments of 105 mm. Assets are can be tracked & traced through SmartLink® or RFID.

Specifications

External (LxWxH):	1200 mm x 1000 mm x 975 mm
Internal (LxWxH):	1140 mm x 940 mm x 790 mm
Weight:	51 kg
Volume:	847 L
Max. Individual Load capacity:	750 kg
Max.Static load on bottom container in a stack:	3200 kg
Max. Dynamic load on bottom container in a stack:	1600 kg
Max. Racking load::	750 kg
Folding Ratio (%):	68.8 %
Folding Height:	295 mm
Base type:	solid base with drainage holes
Wall type:	Solid , Solid
Number of Skids:	2
Number of Feet:	2
Long Side Door, Short Side Door:	Yes , Yes
Handles long side:	1
Handles short side:	1
Drainage holes:	9
Lid available:	Dust cover Drop on
RFID option:	Yes
Material:	PP POM PE (Label Holder)
Temperature range:	-20 °C to 40 °C
Standard Colour:	502 Grey RAL 7040

Packaging





Pallet size: Pallet Height: 1200 mm x 1000 mm 2390 mm

Feature and Benefits

- Easy to use Proven track record, easy to handle
- Foldable design Cost saving when empty. Optimizing vehicle fill return transports.
- smooth design easy to clean, less dirt traps
- drop doors Magnum Optional available with 4 drop doors ensuring an ergonomical emptying of the box.
- Customisation customer logo optionally available
- Versatile Available in multiple heights.
- 100% plastic No metal parts making unit resistant to corrosion.
- bayonet technology easy repair runners
- Optiframe feature adding 105mm to a box allowing boxes to stay foldable when dunnage is inside
- Unique hinge system the unique hinge system makes it easy to fold boxes non sequentially
- ID plates the Optimum ID plates help customers customise and handle their assets
- Label holder optinally available with labelholders;
- strap locations securing loads thanks to strap locations and pins in the base angles.
- Locking devices Handling efficiency operators folding boxes
- Non sequential folding ease of use, allowing to fold box within 5 seconds.

- CO2 reduction - Magnum Optimum ensures optimised payload in road transportation. Reducing reverse logistics costs and lowering CO2 Outstanding performance impact thanks to the best folding ratio on the market.

- SmartLink ready Features locations for RFiD and IoT beacons to ensure efficient track & tracing.
- We grant a 2 year warranty on all purchased products 2 years warranty
- Fully recyclable at the end of its long service life Recyclable

